

# KPC133C

## 21 LEDs Dome Camera



### ● FEATURES

- (1) High resolution for clearer and sharper images
- (2) High sensitivity in the dark environment, 0.4Lux / F2.0, 0Lux (IR ON)
- (3) Day and night features for 24-hour surveillance
- (4) IR LED effective range reaches up to 15 meters

### ● SPECIFICATIONS\*

MODEL	KPC133C
Pick up Element	1/3" H.R. color CCD image sensor
Number of Pixel	771(H) x 492(V) <NTSC> / 753(H) x 582(V) <PAL>
Resolution	High Resolution
Min. Illumination	0.4Lux / F2.0, 0Lux (IR ON)
IR LED	21 units
Effective Range	Up to 15 Meters
S/N Ratio	More than 48dB (AGC off)
Electronic Shutter	1/60 (1/50) to 1/100,000 sec.
Lens	f3.6mm / F2.0
Lens Angle	92.6°
IRIS Mode	AES
White Balance	ATW
Video Output	1.0 Vp-p composite, 75Ω
Power Source (±10%)	DC12V
Current Consumption (±10%)	90mA (IR OFF), 210mA (IR ON)

\* The specifications are subject to change without notice.

\*\* Dimensional Tolerance: ± 5mm

## Good Sensitivity in Low Illumination

KPC13x Series



Conventional



## True Color

KPC13x Series



Conventional

