

# Product datasheet

Specifications



APC Easy Rack PDU, Basic, 0U, 1 Phase, 7.4kW, 230V, 32A, 20 x C13 and 4 x C19 outlets, IEC60309 2P+E inlet

EPDU1132B

## Overview

Lead time Usually in Stock

## Main

|                           |   |
|---------------------------|---|
| Colour                    | Black   |
| Product or component type | PDU   |
| PDU type                  | Basic   |
| Cord length               | 3.00 m  |
| Number of cables          | 1   |
| Provided equipment        | Installation guide<br>Toolless mounting kit<br>Vertical mounting brackets |

## Complementary

|                          |                                     |
|--------------------------|-------------------------------------|
| Input Voltage            | 200 V<br>208 V<br>230 V             |
| Height                   | 117.5 cm                            |
| Width                    | 6.2 cm                              |
| Output Voltage           | 230 V                               |
| Depth                    | 4.44 cm                             |
| Net weight               | 3.58 kg                             |
| Mounting location        | Side                                |
| Mounting preference      | No preference                       |
| Input Plug Type          | IEC 60309 32 A 2P + E               |
| Mounting mode            | Rack-mounted                        |
| Rack units               | 0U                                  |
| Mounting position        | Vertical                            |
| Input current limits     | 32 A                                |
| Load capacity            | 7360 VA                             |
| Network frequency        | 50/60 Hz                            |
| Outlet type and quantity | 20 IEC 60320 C13<br>4 IEC 60320 C19 |

## Environment

|                                       |                                |
|---------------------------------------|--------------------------------|
| Product certifications                | CE<br>TÜV                      |
| Ambient air temperature for operation | 0...45 °C                      |
| Relative humidity                     | 5...95 %                       |
| Operating altitude                    | 0...10000 ft                   |
| Ambient air temperature for storage   | -25...65 °C                    |
| Storage Relative Humidity             | 5...95 %                       |
| Storage altitude                      | 0.000000000...9144.000000000 m |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 132 cm   |
| Package 1 Width              | 16 cm    |
| Package 1 Length             | 11 cm    |
| Package 1 Weight             | 4.351 kg |

## Contractual warranty

|          |                          |
|----------|--------------------------|
| Warranty | 1 year repair or replace |
|----------|--------------------------|

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) 89

Environmental Disclosure [Product Environmental Profile](#)

### Use Better

#### Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

### Use Again

#### Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back No

WEEE  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins