

Product datasheet

Specifications



Power Cord, Locking C19 to Rewireable, 3.0m



AP8759

Overview

Presentation Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.

Lead time Usually in Stock

Main

Product or component type Power cord

Main Output Voltage 240 V

Cable length 3.05 m

Number of cables 1

Physical

Colour Black

Height 23 cm

Width 23 cm

Depth 4.5 cm

Net weight 0.37 kg

Mounting preference No preference

Mounting mode Not rack-mountable

Input

Number of input connectors 1 hard wire 3-wire

Max line current 16 A

Input current limits 16 A

Output

Max current draw 16 A

Number of power socket outlets 1 IEC 60320 C19

Power cable length 3.05 m

Conformance

Product certifications VDE

Environmental

Ambient air temperature for operation	0...70 °C
Relative humidity	20...80 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-20...70 °C
Storage Relative Humidity	20...80 %
Storage altitude	0.0000000000...15240.0000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	23 cm
Package 1 Width	23 cm
Package 1 Length	4.5 cm
Package 1 Weight	0.37 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	25
Package 2 Height	26 cm
Package 2 Width	34 cm
Package 2 Length	57 cm
Package 2 Weight	10 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	25
Package 3 Height	143.99 cm
Package 3 Width	100 cm
Package 3 Length	120 cm
Package 3 Weight	10 kg
SCC14	10731304279829

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) **116**

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard **No**

Packaging without single use plastic **No**

[EU RoHS Directive](#) **Compliant**

SCIP Number **1cdb2fed-a06f-4574-913d-8df8e70936b2**

REACH Regulation [REACH Declaration](#)

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back **Yes**

WEEE  **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**